

SPECIFICATIONS | ACCESSORIES

DISPLAY	Display Screen	7" IPS
	Physical Resolution	1280×800
	Aspect Ratio	16:10
	Brightness	400cd/m ²
	Contrast	800:1
	Viewing Angle	178°/178°(H/V)
INPUT	REF	1
	USB	2
OUTPUT	12G-SDI	2
	3G-SDI	2
	HDMI	1
	FIBER	1 (Optional Module)
	Current	≤2.3 (12V)
POWER	Input Voltage	DC10-15V
	Power Consumption	≤27W
	Built-in Battery	5000mAh
	Operating Temperature	-10°C ~ 60°C
ENVIRONMENT	Storage Temperature	-30°C ~ 70°C
	Dimension(LWD)	264×169×42mm
DIMENSION	Weight	3kg

Note: Due to constant effort to improve products and product features, specifications may change without notice.

12G-SDI Signal Format

Single-link 12G ST 2082-10 Mode 1 Dual-link 2×6G ST 2081-11 Mode 1 Quad-link SQD & 2SI 4×3G-SDI Level A/Level B ST 425-5	4096×2160 3840×2160	23.98p/24p/25p/29.97p/30p 47.95p/48p/50p/59.94p/60p	GBR 4:4:4 10bits
			GBR+A 4:4:4:4 10bits
			YCbCr 4:4:4 10bits
			YCbCr+A 4:4:4:4 10bits
			GBR 4:4:4 12bits
			YCbCr 4:4:4 12bits
YCbCr 4:2:2 12bits			
YCbCr 4:2:2 10bits			

Backward compatible with 6G-SDI/3G-SDI/HD-SDI/SDI signal formats

HDMI Signal Format

HDMI 2.0	4096×2160	23.98p/24p/25p/29.97p/30p
	3840×2160	47.95p/48p/50p/59.94p/60p


Backward compatible with Full HD/HD/SD signal formats



12V 3A Power Adapter



Water-Proof Suitcase



User Manual



Fiber Module (Optional)